











<div style="font-size: 2em; font-weight: bold; border: 2px solid black; border-radius: 50%; width: 40px; height: 40px; display: flex; align-items: center; justify-content: center; margin: 0 auto;">3</div> <div style="font-size: 1.2em; font-weight: bold; margin: 5px 0;">製品記号</div> <div style="font-size: 1.5em; font-weight: bold; margin: 5px 0;">逃し弁</div> <div style="font-size: 0.8em; font-weight: bold; margin: 5px 0;">標準仕様</div> <div style="font-size: 0.8em; font-weight: bold; margin: 5px 0;">価格</div> <div style="font-size: 0.8em; font-weight: bold; margin: 5px 0;">円</div> <div style="font-size: 0.8em; font-weight: bold; margin: 5px 0;">記事</div>	<div style="font-size: 1.2em; font-weight: bold;">SL44E-G□</div>	<div style="font-size: 1.2em; font-weight: bold;">SL24E-B□</div>	<div style="font-size: 1.2em; font-weight: bold;">SL24E-G□</div>																								
	□内には圧力区分の記号が入ります。(下表参照)																										
	<div style="font-weight: bold;">受注品</div> レリーフ弁 1.0MPa  型式: SL-44E型	<div style="font-weight: bold;">受注品</div> FC製 レリーフ弁 1.0MPa  型式: SL-24E型	<div style="font-weight: bold;">受注品</div> FC製 FC製																								
	  		  																								
POINT	ポンプレリーフ用																										
形式	ダッシュポット構造																										
キャップ形式	レバー無																										
適用流体	水・油・液体★ ¹ 注.																										
流体温度	5~80℃★ ²																										
設定圧力範囲	0.035~1.0MPa (設定圧力・流体名をお知らせください)																										
端接続	JIS 10K FFフランジ☆		JIS 10K FFフランジ☆																								
材質	本体	FC																									
	弁体	SUS	FC																								
	弁座	SUS	C3604																								
	バネケース	SUS	SUS																								
ネームプレート色	FC																										
呼び径	本体 FC	要部 C3604	要部 SUS																								
価格	15	56,100	70×70 2.8																								
	20	62,700	75×75 3.3																								
	25	79,200	85×85 4.9																								
	32	93,500	95×90 7																								
	40	103,000	100×95 8.6																								
	50	119,000	110×105 12.4																								
	65		131,000		135×115 26																						
	80		204,000		145×125 36																						
	★ ¹ 流体が灯油など、及び溶剤系の場合はお問い合わせください。 ☆JIS 10K RFフランジも製作しています。 注. 給水装置に使用する場合は、水道法性能基準適合品のSL-38EN、40EN型(64、65頁参照)をご使用ください。		☆JIS 5K FF・RFフランジ、10K RFフランジも製作しています。																								
	■圧力区分 (MPa) <table border="1" style="font-size: 0.8em;"> <tr><th>記号</th><th>圧力区分</th></tr> <tr><td>1</td><td>0.035~0.2</td></tr> <tr><td>2</td><td>0.2を超過0.5</td></tr> <tr><td>3</td><td>0.5を超過1.0</td></tr> </table>		記号	圧力区分	1	0.035~0.2	2	0.2を超過0.5	3	0.5を超過1.0	■圧力区分 (MPa) <table border="1" style="font-size: 0.8em;"> <tr><th>記号</th><th>呼び径65</th><th>呼び径80</th></tr> <tr><td>1</td><td>0.035~0.2</td><td>0.035~0.2</td></tr> <tr><td>2</td><td>0.2を超過0.7</td><td>0.2を超過0.5</td></tr> <tr><td>3</td><td>0.7を超過1.0</td><td>0.5を超過0.8</td></tr> <tr><td>4</td><td></td><td>0.8を超過1.0</td></tr> </table>		記号	呼び径65	呼び径80	1	0.035~0.2	0.035~0.2	2	0.2を超過0.7	0.2を超過0.5	3	0.7を超過1.0	0.5を超過0.8	4		0.8を超過1.0
記号	圧力区分																										
1	0.035~0.2																										
2	0.2を超過0.5																										
3	0.5を超過1.0																										
記号	呼び径65	呼び径80																									
1	0.035~0.2	0.035~0.2																									
2	0.2を超過0.7	0.2を超過0.5																									
3	0.7を超過1.0	0.5を超過0.8																									
4		0.8を超過1.0																									
																											
	★ ² 流体温度5~150℃も製作しています。(油類は150℃以下、温水は90℃以下となります。)																										