



<div style="text-align: center;"> 10 </div> <div style="text-align: center;"> <small>製品記号</small> </div>	JB13-N	JB14-N			
	<small>標準品</small>	<small>標準品</small>			
ベローズ形 伸縮管継手	<small>JIS準拠品 1.0MPa</small>	<small>単式 鋼管用 JIS準拠品 1.0MPa</small>	<small>複式 鋼管用 JIS準拠品 1.0MPa</small>		
					
	<small>型式：JB-13型</small>	<small>型式：JB-14型</small>			
POINT	ベローズ形、JIS準拠品				
標準仕様	<small>形式</small>	<small>ベローズ形</small>			
	<small>形状</small>	<small>単式内圧形</small>	<small>複式内圧形</small>		
	<small>伸び</small>	<small>10mm</small>	<small>20mm</small>		
	<small>縮み</small>	<small>25mm</small>	<small>50mm</small>		
	<small>適用流体</small>	<small>蒸気・空気・不活性ガス・水・温水・油</small>			
	<small>流体温度</small>	<small>220℃以下</small>			
	<small>適用圧力</small>	<small>1.0MPa以下</small>			
	<small>端接続</small>	<small>JIS 10K フランジ注.</small>			
	<small>継手部</small>	<small>圧延鋼材（鋼）フランジ</small>			
	<small>外筒</small>	<small>圧延鋼材（鋼管）</small>			
<small>内筒・ベローズ</small>	<small>SUS316L^{※1.}</small>				
価格 (円)	<small>呼び径</small>	<small>単式</small>	<small>面間寸法 (mm)</small>	<small>複式</small>	<small>面間寸法 (mm)</small>
			<small>梱包質量 (kg)</small>		<small>梱包質量 (kg)</small>
	20	44,000	365	79,600	680
			4.5		6.5
	25	47,400	365	82,600	680
			4.5		6.5
	32	52,800	365	93,600	680
			6		9.5
	40	60,100	365	107,000	680
			6		10
	50	68,400	365	121,000	680
			8		13
	65	76,200	415	146,000	780
			11		19
	80	105,000	415	184,000	780
		13		22	
100	141,000	415	251,000	880	
		17		33	
125	168,000	440	306,000	880	
		23		38	
150	233,000	440	433,000	930	
		30		72	
200	371,000	440	645,000	930	
		56		105	
250	476,000	465	861,000	980	
		68		121	
300	<small>別途お見積り致します。 (受注品)</small>	465	<small>別途お見積り致します。 (受注品)</small>	980	
		104		229	
350	<small>別途お見積り致します。 (受注品)</small>	465	<small>別途お見積り致します。 (受注品)</small>	1030	
		125		268	
記事	<small>注. フランジのガスケット座はRFですが、平面座（座板）の寸法はJIS B 2220 と異なります。 <small>※1. 接液部SUS316L <small>※2. 2.0MPa用は124頁をご参照ください。</small> </small> </small>				

10

ベローズ形伸縮管継手